

## Interactive Floor LED Screen

### IF SERIES



○ 1000x500mm

PIXEL PITCH	P2.976	P3.91	P4.81	P6.25
LED Type	SMD1415	SMD1921	SMD1921	SMD1921
Physical Density	112896dot/m <sup>2</sup>	112896dot/m <sup>2</sup>	43264dot/m <sup>2</sup>	425600dot/m <sup>2</sup>
Module Resolution	84x84dots	84x84dots	52x52dots	32x32dots
Module Size	250x250mm			
Panel Dimension	1000(500)x500(1000)mm			
Panel Weight	25kg			
Maintenance Mode	Front&Back			
Cabinet Frame	Iron/Aluminum			
Brightness	500-700cd/m <sup>2</sup>			
Gray Grade	16bit			
Viewing Angle	120°/120°			
Frame Frequency	≥60Hz			
Refresh Frequency	1920-3840Hz			
Drive Mode	1/40s			
Protection Degree	IP68			
Max Power Consumption	800w/m <sup>2</sup>			
Avg Power Consumption	400w/m <sup>2</sup>			
Power Requirement	AC110-240V 50-60Hz			
Working Temperature	-10-60°C / 10%-90%			
Storage Temperature	-10-60°C / 10%-90%			