

Indoor Transparent LED Screen

TI SERIES



PIXEL PITCH	P2.84	P3.91	P7.81	P10.42	P15.625	P20
LED Type	SMD1921	SMD1921	SMD1921	SMD3535	SMD3535	SMD3535
Physical Density	56320dot/m ²	32768dot/m ²	16384dot/m ²	9216dot/m ²	4096dot/m ²	2304dot/m ²
Module Size	500x125mm	500x125mm	500x125mm	500x125mm	500x125mm	500x125mm
Panel Dimension	1000(500)x500(1000)mm					
Panel Weight	5kg	5kg	6kg	6kg	6kg	6kg
Maintenance Mode	Front&Back					
Cabinet Frame	Aluminum					
Brightness	500-700cd/m ²					
Gray Grade	27bit	16bit	16bit	16bit	16bit	16bit
Viewing Angle	140°/140°					
Frame Frequency	≥60Hz					
Refresh Frequency	1920-3840Hz					
Drive Mode	1/40s					
Protection Degree	IP41	IP30	IP30	IP30	IP30	IP30
Max Power Consumption	800w/m ²					
Avg Power Consumption	200w/m ²					
Power Requirement	AC90-264V 50-60Hz					
Working Temperature	-10~50°C / 10%~85%					
Storage Temperature	-10~50°C / 10%~85%					

Outdoor Transparent LED Screen

DIP SERIES



○ 1000x500mm

PIXEL PITCH	P15.625	P20	P25	P31.25
LED Type	DIP346	DIP346	DIP346	DIP346
Physical Density	4096dot/m ²	2500dot/m ²	1600dot/m ²	1024dot/m ²
Panel Dimension	1000x500(1000)mm			
Panel Weight	9kg			
Maintenance Mode	Front&Back			
Cabinet Frame	Iron/Aluminum			
Brightness	5500-10000cd/m ²			
Gray Grade	14bit			
Viewing Angle	140°/140°			
Frame Frequency	50/60Hz			
Refresh Frequency	1920-3840Hz			
Drive Mode	1/10s	1/10s	1/10s	1/10s
Protection Degree	IP67			
Max Power Consumption	800w/m ²			
Avg Power Consumption	300w/m ²			
Power Requirement	AC110-220V 50-60Hz			
Working Temperature	-10~60°C / 10%~90%			
Storage Temperature	-10~60°C / 10%~90%			